

PROGLAZE SSG BLACK

Version 2.
REVISION DATE: 09/05/2008

Print Date 09/06/2008

SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION

Product Information

Trade name : PROGLAZE SSG BLACK
Product code : 954802 323

Supplier : Tremco Canada division
220 Wicksteed Avenue
Toronto, ON M4H 1G7

Telephone : (416) 421-3300
Emergency Phone: : (613) 996-6666

Product use : Sealant

Preparation Information

Prepared by: : Sewnauth Raghunandan
Date: : 09/05/2008
Telephone : (416) 421-3300

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Black. Non-sag gunnable paste. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.
Eyes : Direct contact may cause moderate irritation.
Ingestion : May cause irritation to the mouth, throat and stomach.
Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Possible skin sensitization. As a by-product of curing up to 4% Methyl Ethyl Ketoxime (MEKO) may be released within product. Repeated and prolonged exposure to MEKO can cause allergic skin reaction. It may adversely affect the blood, (methemoglobinemia and anemia). Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Carbon black is encapsulated by resin and not expected to have adverse effects unless made airborne. Organosilane may cause liver injury with fibrosis after repeated and prolonged overexposure. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Blood, Lung, Liver, Kidney

SECTION 3 : HAZARDOUS INGREDIENTS

Chemical Name	CAS-No.	Weight % Range
Amorphous silica	7631-86-9	3.0 - 7.0
Vinyltrimethoxysilane	2768-02-7	1.0 - 5.0
Carbon Black	1333-86-4	0.1 - 1.0

PROGLAZE SSG BLACK

Version 2.
REVISION DATE: 09/05/2008

Print Date 09/06/2008

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5: FIRE / EXPLOSION HAZARDS

- Flash point : Not available.
- Method : Not available.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form. Silicon oxides and trace amounts of MEKO.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - SPILLS / LEAKS / ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Keep out of water courses. Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Store in sealed containers in a cool, dry, ventilated warehouse location.

SECTION 8 - PREVENTIVE MEASURES/EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection equipment

PROGLAZE SSG BLACK

Version 2.

Print Date 09/06/2008

REVISION DATE: 09/05/2008

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator, as directed by the manufacturer, when the airborne contaminant level(s) exceed the exposure limits indicated on the MSDS.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures** : General ventilation is sufficient.

Exposure Limits

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Amorphous silica	7631-86-9	Ontario TWA:	3 mg/m3	Respirable particles.
		Ontario TWA:	10 mg/m3	Inhalable particulate.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		Ontario TWA:	10 mg/m3	
Carbon Black	1333-86-4	Ontario TWA:	3.5 mg/m3	
		ACGIH TWA:	3.5 mg/m3	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Physical State : Paste
- Form : Non-sag gunnable paste
- Color : Black
- Odor : Oxime
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Negligible
- Evaporation Rate: : Not available.
- Specific Gravity : 1.173
- % Volatile Weight : 1 %

SECTION 10 - REACTIVITY / STABILITY

- Substances to avoid : Strong acids. Strong bases. Alcohols. Water or moisture and oxidizing agents.
- Stability : Material is stable under normal storage, handling, and use.

PROGLAZE SSG BLACK

Version 2.
REVISION DATE: 09/05/2008

Print Date 09/06/2008

Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Amorphous silica, CAS-No.: 7631-86-9
Acute oral toxicity (LD-50 oral) 22,500 mg/kg (Rat) 15,000 mg/kg (Mouse)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Disposal Method : Dispose as hazardous waste according to all local, state, federal and provincial regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:
NOT REGULATED

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

Canadian Regulations:

WHMIS Classification : D2A, D2B
This is a "controlled product" under the Canadian Workplace Hazardous Materials Information System (WHMIS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Other Regulations:

Regulatory VOC (less water and exempt solvent) : 14 g/l



PROGLAZE SSG BLACK

Version 2.
REVISION DATE: 09/05/2008

Print Date 09/06/2008

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	1
Reactivity	0
PPE	

0 = Minimum
1 = Slight
2 = Moderate
3 = Serious
4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Sewnauth Raghunandan

Legend

- ACGIH - American Conference of Governmental Hygienists
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration
- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System